

# ALUAFS<sup>®</sup> Shine


## NON-INSULATED ALUMINIUM FLEXIBLE AIR DUCTS

ALUAFS SHINE non-insulated aluminium flexible air ducts are specifically produced for low and medium pressure heating, cooling, ventilation, exhaust and air conditioning systems.

Airtight ALUAFS SHINE is produced from multi-layer aluminium and metallized polyester, strengthened with high tension hard steel spring wire.

### ALUMINIUM LAMINATED BODY

- Fire retardant: United Kingdom BS 476 Part 6&7
- Impermeable to UV rays
- Highly resistant to UV rays
- 98 % reflective
- Resistant to chemicals



### FLEXIBLE & SEAMLESS CONSTRUCTION

### SMOOTH INNER SURFACE

- Minimal pressure loss

### HIGH TENSION STEEL WIRE

## TECHNICAL PROPERTIES

Construction	1 ply aluminium 2 ply metallized polyester
Available Diameters	Ø 82 mm - Ø 800 mm
Temperature Range	-30 °C / +150 °C
Air Velocity	30 m/s (max)
Operating Pressure	3000 Pa (max)
Standard Length	10 m
Packing	Single cardboard box
Certificate	
Russia	 GOST-R



- Packing in a single cardboard box



- Easy to fit circular, oval or rectangular connectors



**BORU SANAYİ A.Ş.**

İvedik Organize Sanayi Bölgesi  
1468. Cadde (Eski 24) No:153  
Ostim 06370 Ankara / Türkiye  
Phone : +90.312.395 48 60  
Fax : +90.312.395 48 68  
E-mail : export@afs.com.tr  
www.afs.com.tr